

NEW AND STYLISH



4WD 18 HP



SHORTER TURNING
RADIUS



SMART HYDRAULICS
WITH ADDC



DIRECT CONTROL
VALVE



SIDE SHIFT



DUAL PROJECTOR
HEADLAMPS



COMFORTABLE &
ADJUSTABLE SEAT



BONNET WITH
LOCK



MOBILE
CHARGING POINT



TURF, INDUSTRIAL &
AGRICULTURE TYRE
OPTIONS



exports@vst-international.com



www.vst-international.com

SPECIFICATIONS

ENGINE

Power, HP	:	18
No. of Cylinders	:	3
Cubic Capacity, cc	:	900
Max. Torque	:	48.3
Engine RPM	:	2700
Air cleaner	:	Dry Type

POWER TAKE OFF

Power, HP	:	11.1
Pto Std.	:	540

TRANSMISSION

Type	:	Sliding Mesh
No. of Speeds	:	6F + 2R
Rear Axle Reduction Type	:	Bull Gear
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.53 - 17.3
Reverse Speed, kmph	:	1.95 - 8.53
Clutch Type	:	Single

BRAKES

Brake Type	:	Dry Drum type
------------	---	---------------

STEERING TYPE

Type	:	Power Steering
------	---	----------------

SEAT

Type	:	Adjustable driver seat
------	---	------------------------

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	500 Kg
3 Point Linkage	:	CAT-I
Hydraulic Valve Type	:	1SA/1DA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm	:	2945
Width, mm	:	1097
Height, mm	:	2120
Wheelbase, mm	:	1420
Ground Clearance, mm	:	255
Weight, Kg	:	880
Turning Radius, m	:	2.3

OTHER FEATURES

- Downdraft Exhaust
- ROPS (With Beacon lamp)
- Engine Shut-off with Key
- Double acting rear hydraulic remote (DCV)
- Bonnet with Lock
- Battery Cut-off Switch
- Mobile Charger

TYRE

TYRE	FRONT	REAR
Agri	5 x 12	8 x 18
Industrial	23 x 8.5 - 12	33 x 15.5 - 16.5
Turf	23 x 8.5 - 12	33 x 15.5 - 16.5



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%



**COMPACT.
POWERFUL.
UNSTOPPABLE!**



4WD 22 HP



SIDE SHIFT



SHORTEST TURNING
RADIUS IN ITS
CATEGORY



SMART HYDRAULICS
WITH ADDC



DUAL PROJECTOR
HEADLAMPS



HEAVY DUTY
FRONT AXLE



DIRECT CONTROL
VALVE



COMFORTABLE &
ADJUSTABLE SEAT



MOBILE
CHARGING POINT



BONNET WITH
LOCK



TURF, INDUSTRIAL &
AGRICULTURE TYRE
OPTIONS



exports@vst-international.com



www.vst-international.com

SPECIFICATIONS

ENGINE

Power, HP	:	22
No. of Cylinders	:	3
Cubic Capacity, cc	:	980
Max. Torque	:	54
Engine RPM	:	3000
Air cleaner	:	Dry Type

POWER TAKE OFF

Power, HP	:	12.2
Pto Std.	:	540

TRANSMISSION

Type	:	Sliding Mesh
No. of Speeds	:	6F + 2R
Rear Axle Reduction Type	:	Bull Gear
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.7-19.2
Reverse Speed, kmph	:	2.2-9.5
Clutch Type	:	Single

BRAKES

Brake Type	:	Dry Drum type
------------	---	---------------

STEERING TYPE

Type	:	Power Steering
------	---	----------------

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	500
3 Point Linkage	:	CAT-I
Hydraulic Valve Type	:	ISA/IDA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm	:	2945
Width, mm	:	1130
Height, mm	:	2330
Wheelbase, mm	:	1420
Ground Clearance, mm	:	267
Weight, Kg	:	880
Turning Radius, m	:	2.3

OTHER FEATURES

- Downdraft Exhaust
- ROPS (With Beacon lamp)
- Engine Shut-off with Key
- Rear View Mirror
- Battery Cut-off Switch
- Mobile Charger

TYRE

TYRE	FRONT	REAR
Agri	6 x 12	8.3 x 20
Industrial	23 x 8.5 - 12	33 x 15.5 - 16.5
Turf	23 x 8.5 - 12	33 x 15.5 - 16.5



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%



YOUR TRUSTED PARTNER FOR LIFE



4WD 24 HP



POWER PACKED
4-CYLINDER
STAGE-V ENGINE



750 KG SMART
HYDRAULICS WITH
ADDC



BALANCED
POWER STEERING



OIL IMMERSED
BRAKE



DIRECT CONTROL
VALVE



HEAVY DUTY
FRONT AXLE



DUAL PROJECTOR
LAMP



BONNET WITH
LOCK



MOBILE
CHARGER



COMFORTABLE &
ADJUSTABLE SEAT



SPECIFICATIONS

ENGINE

Power, HP	:	24
No. of Cylinders	:	4
Cubic Capacity, cc	:	1306
Max. Torque	:	72.2
Engine RPM	:	2700
Air cleaner	:	Dry Type

POWER TAKE OFF

Power, HP	:	17.2
Pto Std.	:	540

TRANSMISSION

Type	:	Constant Mesh
No. of Speeds	:	8F + 2R
Rear Axle Reduction Type	:	Bull Gear
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.51 - 18.44
Reverse Speed, kmph	:	1.35 - 4.9
Clutch Type	:	Single

BRAKES

Brake Type	:	OIB
------------	---	-----

STEERING TYPE

Type	:	Power Steering
------	---	----------------

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	750
3 Point Linkage	:	CAT-I
Hydraulic Valve Type	:	1SA/1DA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm	:	2995
Width, mm	:	1080
Height, mm	:	2075
Wheelbase, mm	:	1520
Ground Clearance, mm	:	267
Weight, Kg	:	939
Turning Radius, m	:	2.1

OTHER FEATURES

- Downdraft Exhaust
- ROPS (With Beacon lamp)
- Engine Shut-off with Key
- Rear View mirrors
- Battery Cut-off Switch
- Mobile Charger

TYRE

TYRE	FRONT	REAR
Agri	6 x 12	8.3 x 20
Radial	180/85 - D12	280/70R 20



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%



TECHNO-COMPACT TRACTOR



932 DI

VST FIELDTRAC



4WD 30HP

STAGE V



Japanese Technology
Driven IDI Engine



High
Torque



Dual Acting
Power Steering



Superior Styling with
Great Ergonomics



Front Bonnet
with Lock



Multi-Applications
Suitability



+91- 7540008117

connect@vsttractors.com

www.vsttractors.com

**932 DI****STAGE V****TECHNICAL SPECIFICATION****ENGINE**

Power, HP	30
No. Of cylinders	3
Cubic Capacity, cc	1642
Max. Torque, mm	109.4
Engine RPM	2500

TRANSMISSION

No. of Speeds	9+3
Type	Synchromesh
Speeds, Kmh	1.81 - 22.32
Shift Type	Side Shift

POWER TAKE OFF

Power, HP	24
No. of Speeds	3
Mid PTO	Yes

HYDRAULICS

Type	ADDC
Lift Capacity	1250 @ Hitch Point
3 Point Linkage	Cat 1 N

TYRE

Front - Agri, STD	6x12
Rear - Agri, STD	9.5 x 20

WEIGHTS & DIMENSIONS

Weight, Kg	1348
Length, mm	2990
Width, mm	1245
Wheel Base, mm	1520
Groud Clearance, mm	325
Turning Radius, m	2.1

Trust of >7 Lakh Farmers,
Legacy of > 50 YearsWidest Working Range
(17 HP to 50 HP)No.1 Power Tiller
Brand1st 4WD
Compact TractorGlobal Footprints
in > 40 CountriesYear on Year
Growth Rate of over 20%

Disclaimer : VST reserves the right to modify specifications as needed to meet company requirements.

**TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: connect@vsttractors.com
CIN: L34101KA1967PLC001706. www.vsttractors.com

**+91- 7540008117**

/vsttillers



/company/vst-tillers

<http://bit.ly/VSTVideos>

Disclaimer : Pictures used here are for illustration purpose only. Product specification are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

